

Material Safety Data Sheet

May be used to comply with OSHA's Hazard Communication Standard, 29 CFR 1910.1200. Standard must be consulted for specific requirements.

U.S. Department of Labor

Occupational Safety & Health Administration
(Non-Mandatory Form)
Form Approved
OMB No. 1218-0072



IDENTITY (As Used on Label and List)

A-800 Invisible

Re-Admission Ink

Section I

Manufacturer's Name UVP, INC.	Emergency Telephone Number (800) 457-4280
Address (Number, Street, City, State, and ZIP Code) 2066 W. 11TH STREET UPLAND, CA 91786	Telephone Number for Information (800) 452-6788 OR (909) 946-3197
	Date Prepared 1 / 1 / 2005
	Signature of Preparer (optional)

Section II - Hazard Ingredients/Identity Information

Hazardous Components (Specific Chemical Identity; Common Name(s))	OSHA PEL	ACGIH TLV	%(optional)
Urea - Formaldehyde Resin	*	*	2.60%
Normal Butyl Alcohol	100	50	1.60%
Xylene	100	*	1.00%
Isopropyl Alcohol	400	400	60.00%
Denatured Alcohol	1000	1000	25.00%
Methyl - 7 - Diethylaminocoumarin	8	8	5.00%
Aminocoumarin Derivatives	*	*	0.30%
Frangrance Compound	*	*	0.30%
*NOT LISTED			

Section III - Physical/Chemical Characteristics

Boiling Point	179 degrees F	Specific Gravity (H ₂ O = 1)	0.8
Vapor Pressure (mm Hg.) At 68 Degree F	33	Melting Point	N/A
Vapor Density (AIR = 1)	1.6	Evaporation Rate (Butyl Acetate = 1)	2

Solubility in Water
Miscible up to 30 %

Appearance and Odor
Liquid, aromatic odor

Section IV - Fire and Explosion Hazard Data

Flash Point (Method Used) Tag open cup 65 degrees F		Flammable Limits LEL 2%	UEL 19%
--	--	----------------------------	------------

Extinguishing Media
Dry Chemical

Special Fire Fighting Procedures
None

Unusual Fire and Explosion Hazards
None

(Reproduce locally)

Section V - Reactivity Data **A-800**

Stability	Unstable		Conditions to Avoid
	Stable	X	

Incompatibility (*Materials to Avoid*)
 Strong Oxidizing Agents

Hazardous Decomposition or Byproducts
 Thermal decomposition may produce carbon monoxide and/or carbon dioxide

Hazardous Polymerization	May Occur		Conditions to Avoid
	Will Not Occur	X	N/A

Section VI - Health Hazard Data

Route(s) of Entry:	Inhalation?	Skin?	Ingestion?
Eyes: Yes	Yes	Yes	Yes

Health Hazards (*Acute and Chronic*)
 No information available

Carcinogenicity:	NTP?	IARC Monographs?	OSHA Regulated?
	No	No	No

Signs and Symptoms of Exposure
 EYES:Irritation, Redness, Tearing, Blurred Vision. INHALATION:Many Symptoms, Even Asphyxiation,
 SKIN:Dryness. INGESTION:Nausea, Vomiting abdominal pain
 Medical Conditions No information available
 Generally Aggravated by Exposure

Emergency and First Aid Procedures INGESTION:induce vomiting Call DR.
 EYES:Flush with large amount of water. INHALATION:Remove to fresh air, if breathing is difficult
 administer oxygen, call a physician. SKIN:Wash with soap and water.

Section VII - Precautions for Safe Handling and Use

Steps to Be Taken in Case Material is Released or Spilled
 Eliminate all sources of ignition, Absorb liquid on paper, vermiculit or other absorbent material. If TLV
 is exceeded, a respirator with a noganic vapor cartridge is recommended.

Waste Disposal Method
 Dispose of contaminated absorbet in conformance with regulation in your locality.

Precautions to Be taken in Handling and Storing
 WARNING!!!! FLAMMABLE, Keep away from heat, sparks and open flames.
 DO NOT LEAVE CONTAINER OPEN
 Other Precautions
 Use with adequated ventilation.

Section VIII - Control Measures

Respiratory Protection (<i>Specify Type</i>)		
Not Required		
Ventilation	Local Exhaust	Special
	Not Required	NONE
Protective Gloves	Mechanical (<i>General</i>)	Other
	Recommended	NONE
Not Required	Eye Protection	
Other Protective Clothing or Equipment	Goggles Recommended	
NONE		